


PROPRIETARY INFORMATION NOTICE
 This document and the designs, specifications, and engineering information disclosed herein are the property of Parlex USA LLC, and are not to be disseminated or reproduced without expressed written consent. This document is loaned in confidence and then only for consideration of the matter disclosed herein. In accepting loan of this document, the recipient agrees to keep it and the matter disclosed herein in confidence and not to use or permit their use in any way detrimental to Parlex USA LLC.



CABLE MARKING:
 PARLEX XXXX (Date code)
 UL STYLE 20566 105°C
 ROHS

NOTES:

CONDUCTOR SPACING = 1.27mm (0.050"±0.005")
 CONDUCTORS REQ'D PER ASSY = XX
 CONDUCTORS = .003" THK. x .026" WIDE COPPER
 OUTER COND. = .003" THK. x .026" WIDE TINNED CU.
 CABLE THICKNESS = .010"±.002"
 CABLE WIDTH = (.05" x [XX + 1]) ±.005"
 INSULATION = 2 MIL POLYESTER w/ 1.5 MIL FLAME
 RETARDANT ADHESIVE

AMP RECEPTACLE CONTACTS = 1-487547-1
 AMP LATCH STYLE HSGS = 487545 Series
 AMP PLAIN STYLE HSGS = 487544 Series
 AMP SOLDER TAB CONTACTS = 487923-4

TEMP RATING = -55°C to 105°C
 VOLTAGE RATING = 300V
 DIELECTRIC STRENGTH = 2500 VOLTS/MIL
 U.L. FLAME RATING = VW-1 (UL 20566)
 INSULATION RESISTANCE = 1000 MEGOHMS, MIN
 PER IPC-TM-650, METHOD 2.6.3.2 @ AMBIENT TEMP.

TOLERANCES ON LENGTHS:
 0-3" ±.050" 12"-18" ±.110"
 3"-6" ±.060" 18"-24" ±.120"
 6"-12" ±.070" 24"-36" ±.150"

36" or greater tol = ±1% of length.

P/N WHEN ORDERING:

2797 A XX - XXXX -

REPRESENTS CABLE CONFIGURATION (A - F)
 NOTE: STYLES C & D ARE PLAIN CONNECTORS

NUMBER OF CONDUCTORS (1 - 99)

DESIRED CABLE LENGTH IN mm's.
 4 PLACES MAXIMUM. NO DECIMAL PTS.
 EXAMPLE: 343 (L=13.500")
 140 (L=5.512")

DRAWING REVISION

15 SPACES MAX.
 P/N EXAMPLES:

2797A15-343 -

0.050"±.005" centerline to centerline spacing
 15 conductor cable
 Cable Length = 13.500"±0.110"
 Latch connectors, same side orientation
 Amp connector p/n 1-487545-2 (Refer to Amp catalog for p/n's on different # of positions)



1.27MM CABLE ROHS COMPLIANT

SIZE B	FSCM 18377	PS-2797	Rev. -
SCALE	1:1	SHEET OF	