

Characteristics:

Long life, low noise and high reliability

**Specifications:**

Dimensions (mm)	: Ø 61.0 X 32.0 X 77.0 mm
Shaft Diameter (mm)	: Ø 6.350 mm
Input Voltage (V)	: 230.0 V
No Load Speed (rpm)	: 2900 rpm
No Load Current (A)	: 0.41 A
Nominal Speed (rpm)	: 2700 rpm
Nominal Torque (mNm)	: 20.00 mNm
Nominal Current (A)	: 0.44 A
Stall Torque (mNm)	: 37.00 mNm
Stall Current (A)	: 0.66 A
Maximum Output Power (W)	: 17.30 W
Maximum Efficiency (%)	: 25%
Torque (mNm) - Max Eff	: 69.00 mNm
Speed (rpm) - Max Eff	: 2367 rpm
Life (Typical)	: 200 hr
Weight (g)	: 948 g
Operating Temperature Range (°C)	: -10 to 55 °C
Storage Temperature Range (°C)	: -20 to 80 °C
Electrical Connection	: Terminals

Performance Data:

	No Load	Stall	Max Efficiency	Max Power
Current (A)	0.41	0.66	0.56	0.57
Efficiency (%)	-	-	25.30	25.00
Output Power (W)	-	-	17.00	17.30
Speed (rpm)	2900.00	-	2367.00	2278.00
Torque (mNm)	-	37.00	69.60	72.50

Application Examples:

Nebulizers

